



POWER ENTRANCE: 240V, 70A, 60Hz, SINGLE PH. (TWO #6 + ONE #2 EARTH GND REQUIRED) (OTHER VOLTAGES AVAILABLE UPON REQUEST)

AIR INLET: 3/8" NPT (40PSI MIN., BULKHEAD PROVIDED) FILTER, REGULATOR, AND SHUT OFF PROVIDED ON SUBPANEL INSIDE PANEL ENCLOSURE.

NOTE: TESTER CAN BE SUPPLIED WITH OR WITHOUT POWER PANEL WHICH CAN BE LOCATED ON EITHER END OF TESTER.

**- REFERENCES AND REVISIONS -**

REV. NO.	DATE	DESCRIPTION	REMARKS	BY:

This drawing is proprietary information and considered intellectual property of Hanco International. Unauthorized reproducing, electronic transmission, or distribution without written authorization of Hanco International is prohibited.

**HANCO INTERNATIONAL**  
 DIVISION OF THE HANNON COMPANY  
 1605 WAVERSBURG DR. SE  
 CANTON, OHIO, U.S.A. 44707  
 PH: 330/456-4728 FAX: 330/456-3323

TITLE:  
**MODEL SST15014V SWITCH STICK TESTER**  
**DIMENSIONAL DRAWING**

DATE: 6-13-1994  
 DRAWN BY: TOM WHIPKEY  
 SCALE: 1/4" = 1'  
 SERIES: DA  
 SHEET: 1 OF 1  
 DRAWING NO.: A8877