



NOTE 1: 240 VOLT, 60Hz, SINGLE PHASE POWER ENTRANCE.
(TWO #6 PLUS ONE #2 EARTH GROUND IN 1 1/2" CONDUIT)
OTHER VOLTAGE INPUTS AVAILABLE UPON REQUEST.

NOTE 2: 3/8" NPT AIR INLET (60 PSI MINIMUM, BULKHEAD FITTING PROVIDED) FILTER, REGULATOR, AND SHUT OFF PROVIDED ON SUBPANEL INSIDE POWER PANEL CABINET.

APPOX. SHIPPING WEIGHT: 3700 LBS.

- REFERENCES AND REVISIONS -

REV. NO.	DATE	DESCRIPTION	REMARKS	BY:

This drawing is proprietary information and considered intellectual property of Hanco International. Unauthorized reproducing, electronic transmission, or distribution without written authorization of Hanco International is prohibited.

HANCO INTERNATIONAL
DIVISION OF THE HANNON COMPANY
1605 WAVERSBURG DR. SE
CANTON, OHIO, U.S.A. 44707
PH: 330/456-4728 FAX: 330/456-3323

TITLE:
**6- POSITION HOSE AND HOOD TESTER
WITH DA SERIES POWER PANEL**

DATE:	2-22-1997	SCALE:	1/4" = 1'	SHEET:	1 OF 1
DRAWN BY:	TOM WHIPKEY	SERIES:	DA	DRAWING NO.:	A9039