



1. POWER ENTRANCE: 240 VOLT 60HZ. SINGLE PHASE (TWO #6 PLUS ONE #2 EARTH GROUND WIRE IN 1 1/2" CONDUIT) OTHER VOLTAGE INPUTS AVAILABLE UPON REQUEST.
 2. AIR INPUT: 3/8" NPT (60 PSI MINIMUM. BULKHEAD FITTING PROVIDED) SHUTOFF PROVIDED ON SUBPANEL INSIDE POWER PANEL CABINET.
 3. WATER INPUT: 1/2" NPT (50PSI MINIMUM) BULKHEAD FITTING. AND INLINE WATER FILTER PROVIDED
- NOTE 1: THE FLOOR DRAIN MAY BE LOCATED ANYWHERE WITHIN 25 FEET OF THE TEST TANK, BUT GENERALLY IS LOCATED WITHIN THE TEST COMPARTMENT.
- NOTE 2: DRAIN HOSE END MUST BE SECURED TO PREVENT "WHIPPING"
- NOTE 3: MACHINE MUST BE SEPERATED FOR SHIPPING (THREE PIECES)

GLOVE POSITIONS PER SIDE	"A"	B"	APPROX. SHIPPING WEIGHT
6	7'-7"	3'-9 1/2"	6700 LBS.
8	9'-1"	4'-6 1/2"	7100 LBS.
10	10'-7"	5'-3 1/2"	7500 LBS.
12	12'-1"	6'-1 1/2"	7900 LBS.
14	13'-7"	6'-9 1/2"	8300 LBS.

- REFERENCES AND REVISIONS -

REV.	DATE:	REMARKS:	BY:
A	3-2-2009	UPDATED TO NEW TALL ACCESS DOOR	BAF

This drawing is proprietary information and considered intellectual property of Hanco International. Unauthorized reproducing, electronic transmission, or distribution without written authorization of Hanco International is prohibited.

HANCO INTERNATIONAL
 DIVISION OF THE HANNON COMPANY
 1605 WAINESBURG DR. SE
 CANTON, OHIO, U.S.A. 44707
 PH: 330/456-4728 FAX: 330/456-3323

TITLE:
MODEL "DA" DUAL GLOVES/SLEEVE TESTER
W/ CORNER POWER PANEL
 DIMENSIONAL DRAWING

DATE: 2-24-1997
 SCALE: 1/4" = 1'
 SHEET: 1 OF 1
 DRAWN BY: TOM WHIPKEY
 SERIES: DA
 DRAWING NO.: A9040